


DALI  
Dimmable

Dimmable

Dimmable  
0/1...10

Part Number	Output V	Output@230V I max	W @230V	Output@110V I max	W @110V	Dimensions A x B x C	Protocol	05
A40PBX075D0B	12V/DC	6,25A	75W	5A	60W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH	
A40PBX7524DB	24V/DC	3,12A	75W	2,5A	60W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH	
A40PBX100D0B	24V/DC	4,16A	100W	2,5A	60W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH	•
A40PBX150D0B	24V/DC	6,25A	150W	3,12A	75W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH	•
A40PBX200D0B	24V/DC	8,33A	200W	3,75A	90W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH	



Datasheet download

### Alimentatore LED dimmerabile DALI/0-10V/1-10V/Push

- Alimentatore indipendente - IP20 - Classe II di isolamento
  - Comando DALI o pulsante (sul secondario, con memoria), 0-10V, 1-10V o potenziometro, selezionabile tramite impostazione dei dip-switches.
  - Possibilità di sincronizzare più alimentatori
  - Uscita in tensione costante 12/24V PWM
  - Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
  - Morsetti rapidi
  - Doppio morsetto d'uscita
  - Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
  - Alimentazione: 110÷240V/AC - Uscita stabilizzata.
- A richiesta, alimentazione a 230VDC o specifica potenziata a 110V

### Dimmable LED Driver DALI/0-10V/1-10V/Push

- For independent use - IP20 - Insulation class II
  - Dimming control by DALI or PUSH (on the secondary, with memory), 0-10V, 1-10V or potentiometer, selecting the dipswitch combination on board.
  - Possible synchronization of more drivers
  - Output in constant voltage 12/24V PWM
  - Self-resetting protection against overtemperatures, open circuit and against output short circuits
  - Fast terminals
  - Double output.
  - Cable clamp for flat and round cables
  - Input voltage: 110÷240V/AC - Steady output.
- On request, 230VDC input voltage or specific boosted 110V version