

Foxbridge IP20 Surface Mount PIR Sensor with Adjustable Detection Range

Part Code: 70405

Our range of Foxbridge Sensors celebrate BELL's history and show our commitment to providing solutions in the LED market.

- Tailored detection zone
- Detection area can be adapted using the included detection shields
- Wide detection range - walk across detection up to 12m
- Easy to adjust lux and time delay settings
- Detection moving speed 0.6-1.5ms



Convenient
Solutions



Easy
Installation



Multiple
Sensor Options



Optional
Accessories



Product Category Fittings / Fittings Accessories

Application Sensor

Product Warranty 5 Years

EAN 5013588002088

Commodity Code 8504318050

Country of Origin CN

Technical Specification

Volts (V)	200/220
Frequency (Hz)	50/60
IP Rating	IP20
Operating Temperature	-20°C - +35°C

Packaging Information

Minimum Order Quantity	1
Height (mm)	38
Diameter (mm)	80
Cut Out (mm)	73mm (Recessed Mount)
Individual Product Weight (kg)	0.116
Single Box Weight (kg)	0.12
Single Box Height (mm)	92
Single Box Width (mm)	57
Single Box Depth (mm)	90
Single Box Volume	0.00047196
Outer Box Qty	50
Outer Box Weight (kg)	6.8
Outer Box Height (mm)	490
Outer Box Width (mm)	320
Outer Box Depth (mm)	200
Outer Box Volume	0.03136
UNSPSC Code	39122236

Construction

Primary Material	Flame Retardant Polycarbonate
------------------	-------------------------------

Controls

Sensor Detection Angle	360°
Sensor Hold Time	10s to 7min - Dial

Electrical Information

Electric Class	Class II
----------------	----------

Installation Information

Mounting Options	Surface
Mounting Height	2.2 - 4m