

Inda Blank Section

IND-BLANK IND-BLANK

Inda interlock blank section 228mm

- Blank section for Inda battens
- Quick and easy to install
- 228x288mm



Technical Summary	
Product Code	IND-BLANK
Conduit Entry 20mm	TRUE



General Information

Materials	Housing polycarbonate and powder coated steel
Installation Area	Internal

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK

Inda Blank Section

IND- IND-BLANK

Overview

Blank section for Inda battens



General Information

Materials	Housing polycarbonate and powder coated steel
Installation Area	Internal

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Inda Blank Section

IND4F-BLANK IND4F-BLANK

Blank section for 4ft Inda batten

- Blank section for 4ft batten
- Quick and easy to install
- 1274x228mm



Technical Summary	
Product Code	IND4F-BLANK



General Information

Installation Internal
Area

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Inda Blank Section

IND4F-IND4F-BLANK

Overview

Blank section for Inda battens



General Information

Installation	Internal
Area	

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only


Inda

Kosnic

IND4F38/DV IND4F38/DV

Inda slim backlight batten 4ft 22/38W CCT switch 1-10VDim

- Switchable wattage and CCT switchable (3000K/4000K/5000K)
- Emergency options available
- Optional plug-in PIR ON/OFF sensor compatible with Uni-Remote
- DALI-2 DT 6, DSI, switchDIM, corridor FUNCTION V2 option available
- 228mm blank section with knock out sections to fit in motion sensor and EME downlight
- 1-10 (0-10V) dimming
- 20mm conduit entry
- Included 2.0m drop suspension kit



Overview

The slim backlight Inda batten is CCT switchable and 1-10V/0-10V dimmable. With multiple wattage, DALI dimming, side mounted sensors and integrated emergency options. If you want to keep the slim design on show, multiple fittings can be joined with blank sections which can be fitting with sensors or emergency downlights.

General Information

Materials	Housing polycarbonate and powder coated steel
Installation Area	Internal

Technical Summary

Product Code	IND4F38/DV
Conduit Entry 20mm	TRUE

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK

KosnicLightingUK

7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Overview

The slim backlight Inda batten is CCT switchable and 1-10V/0-10V dimmable. With multiple wattage, DALI dimming, side mounted sensors and integrated emergency options. If you want to keep the slim design on show, multiple fittings can be joined with blank sections which can be fitting with sensors or emergency downlights.



General Information

Materials	Housing polycarbonate and powder coated steel
Installation Area	Internal

Inda

IND4F38ND4F38/DV



Optional Gear

Product Code	Description	Type
MWS-REC/DV	Recessed microwave Sensor, 1-10V dim output, remote required	Microwave Sensor
NTR03/ST	Nitro Emergency Downlight 3W Self-test White	Emergency Light
NTR03	Nitro Emergency Downlight 3W Manual test White	Emergency Light
MWS-SID/DV	M31 Side-Mount 1-10V microwave motion sensor MC054V RC	Microwave Sensor
MWS-SID	M30 Side-mount microwave motion ON/OFF sensor	Microwave Sensor
PIR-SID	P30 Exterior PIR Sensor Side-Mount with RMT-UNI control	PIR Sensor

Accessories

Product Code	Description	Type
IND-BLANK	Inda interlock blank section 228mm	Connector kit
IND4F-BLANK	Blank section for 4ft Inda batten	

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only


Inda

Kosnic

IND4F38/DV/E IND4F38/DV/E

Inda slim backlight batten 4ft 22/38W CCT switch 1-10VDim EME

- Switchable wattage and CCT switchable (3000K/4000K/5000K)
- Emergency options available
- Optional plug-in PIR ON/OFF sensor compatible with Uni-Remote
- DALI-2 DT 6, DSI, switchDIM, corridor FUNCTION V2 option available
- 228mm blank section with knock out sections to fit in motion sensor and EME downlight
- 1-10 (0-10V) dimming
- 20mm conduit entry
- Included 2.0m drop suspension kit



Overview

The slim backlight Inda batten is CCT switchable and 1-10V/0-10V dimmable. With multiple wattage, DALI dimming, side mounted sensors and integrated emergency options. If you want to keep the slim design on show, multiple fittings can be joined with blank sections which can be fitting with sensors or emergency downlights.

General Information

Materials	Housing polycarbonate and powder coated steel
Installation Area	Internal

Technical Summary

Product Code	IND4F38/DV/E
Conduit Entry 20mm	TRUE

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK

KosnicLightingUK

7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Overview

The slim backlight Inda batten is CCT switchable and 1-10V/0-10V dimmable. With multiple wattage, DALI dimming, side mounted sensors and integrated emergency options. If you want to keep the slim design on show, multiple fittings can be joined with blank sections which can be fitting with sensors or emergency downlights.



General Information

Materials	Housing polycarbonate and powder coated steel
Installation Area	Internal

Inda

IND4F38NDWE38/DV/E



Optional Gear

Product Code	Description	Type
MWS-REC/DV	Recessed microwave Sensor, 1-10V dim output, remote required	Microwave Sensor
NTR03/ST	Nitro Emergency Downlight 3W Self-test White	Emergency Light
NTR03	Nitro Emergency Downlight 3W Manual test White	Emergency Light
MWS-SID/DV	M31 Side-Mount 1-10V microwave motion sensor MC054V RC	Microwave Sensor
MWS-SID	M30 Side-mount microwave motion ON/OFF sensor	Microwave Sensor
PIR-SID	P30 Exterior PIR Sensor Side-Mount with RMT-UNI control	PIR Sensor

Accessories

Product Code	Description	Type
IND-BLANK	Inda interlock blank section 228mm	Connector kit
IND4F-BLANK	Blank section for 4ft Inda batten	

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Inda Blank Section

IND5F-BLANK IND5f-BLANK

Blank section for 5ft Inda batten

- Blank section for 5ft batten
- Quick and easy to install
- 1574x228mm



Technical Summary	
Product Code	IND5f-BLANK



General Information

Installation Area Internal

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Inda Blank Section

IND5F-IND5f-BLANK

Overview

Blank section for Inda battens



General Information

Installation	Internal
Area	

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only

Overview

The slim backlight Inda batten is CCT switchable and 1-10V/0-10V dimmable. With multiple wattage, DALI dimming, side mounted sensors and integrated emergency options. If you want to keep the slim design on show, multiple fittings can be joined with blank sections which can be fitting with sensors or emergency downlights.



General Information

Materials	Housing polycarbonate and powder coated steel
Installation Area	Internal

Inda

IND5F50/DA IND5F50/DA

Inda Slim backlight batten 5ft 28/50W CCT switch DALI

- Switchable wattage and CCT switchable (3000K/4000K/5000K)
- Emergency options available
- Optional plug-in PIR ON/OFF sensor compatible with Uni-Remote
- DALI-2 DT 6, DSI, switchDIM, corridor FUNCTION V2 option available
- 228mm blank section with knock out sections to fit in motion sensor and emergency downlight
- 1-10 (0-10V) dimming
- 20mm conduit entry
- Included 2.0m drop suspension kit



Technical Summary

Product Code	IND5F50/DA
Conduit Entry 20mm	TRUE

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK



7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Overview

The slim backlight Inda batten is CCT switchable and 1-10V/0-10V dimmable. With multiple wattage, DALI dimming, side mounted sensors and integrated emergency options. If you want to keep the slim design on show, multiple fittings can be joined with blank sections which can be fitting with sensors or emergency downlights.



General Information

Materials	Housing polycarbonate and powder coated steel
Installation Area	Internal

Inda

IND5F50/DA



Optional Gear

Product Code	Description	Type
MWS-REC/DV	Recessed microwave Sensor, 1-10V dim output, remote required	Microwave Sensor
NTR03/ST	Nitro Emergency Downlight 3W Self-test White	Emergency Light
NTR03	Nitro Emergency Downlight 3W Manual test White	Emergency Light
MWS-SID/DV	M31 Side-Mount 1-10V microwave motion sensor MC054V RC	Microwave Sensor
MWS-SID	M30 Side-mount microwave motion ON/OFF sensor	Microwave Sensor
PIR-SID	P30 Exterior PIR Sensor Side-Mount with RMT-UNI control	PIR Sensor

Accessories

Product Code	Description	Type
IND-BLANK	Inda interlock blank section 228mm	Connector kit

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only

Overview

The slim backlight Inda batten is CCT switchable and 1-10V/0-10V dimmable. With multiple wattage, DALI dimming, side mounted sensors and integrated emergency options. If you want to keep the slim design on show, multiple fittings can be joined with blank sections which can be fitting with sensors or emergency downlights.



General Information

Materials	Housing polycarbonate and powder coated steel
Installation Area	Internal

Inda

IND5F50/DA/E IND5F50/DA/E

Inda Slim backlight batten 5ft 28/50W CCT switch DALI EME

- Switchable wattage and CCT switchable (3000K/4000K/5000K)
- Emergency options available
- Optional plug-in PIR ON/OFF sensor compatible with Uni-Remote
- DALI-2 DT 6, DSI, switchDIM, corridor FUNCTION V2 option available
- 228mm blank section with knock out sections to fit in motion sensor and eme downlight
- 1-10 (0-10V) dimming
- 20mm conduit entry
- Included 2.0m drop suspension kit



Technical Summary

Product Code	IND5F50/DA/E
Conduit Entry 20mm	TRUE

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK



7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Overview

The slim backlight Inda batten is CCT switchable and 1-10V/0-10V dimmable. With multiple wattage, DALI dimming, side mounted sensors and integrated emergency options. If you want to keep the slim design on show, multiple fittings can be joined with blank sections which can be fitting with sensors or emergency downlights.



General Information

Materials	Housing polycarbonate and powder coated steel
Installation Area	Internal

Inda

IND5F50ND5E/DA/E



Optional Gear

Product Code	Description	Type
MWS-REC/DV	Recessed microwave Sensor, 1-10V dim output, remote required	Microwave Sensor
NTR03/ST	Nitro Emergency Downlight 3W Self-test White	Emergency Light
NTR03	Nitro Emergency Downlight 3W Manual test White	Emergency Light
MWS-SID/DV	M31 Side-Mount 1-10V microwave motion sensor MC054V RC	Microwave Sensor
MWS-SID	M30 Side-mount microwave motion ON/OFF sensor	Microwave Sensor
PIR-SID	P30 Exterior PIR Sensor Side-Mount with RMT-UNI control	PIR Sensor

Accessories

Product Code	Description	Type
IND-BLANK	Inda interlock blank section 228mm	Connector kit

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only


Inda

Kosnic

IND5F50/DV IND5F50/DV

Inda slim backlight batten 5ft 28/50W CCT switch 1-10V Dim

- Switchable wattage and CCT switchable (3000K/4000K/5000K)
- Emergency options available
- Optional plug-in PIR ON/OFF sensor compatible with Uni-Remote
- DALI-2 DT 6, DSI, switchDIM, corridor FUNCTION V2 option available
- 228mm blank section with knock out sections to fit in motion sensor and EME downlight
- 1-10 (0-10V) dimming
- 20mm conduit entry
- Included 2.0m drop suspension kit



Overview

The slim backlight Inda batten is CCT switchable and 1-10V/0-10V dimmable. With multiple wattage, DALI dimming, side mounted sensors and integrated emergency options. If you want to keep the slim design on show, multiple fittings can be joined with blank sections which can be fitting with sensors or emergency downlights.

General Information

Materials	Housing polycarbonate and powder coated steel
Installation Area	Internal

Technical Summary

Product Code	IND5F50/DV
Conduit Entry 20mm	TRUE

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK

7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Overview

The slim backlight Inda batten is CCT switchable and 1-10V/0-10V dimmable. With multiple wattage, DALI dimming, side mounted sensors and integrated emergency options. If you want to keep the slim design on show, multiple fittings can be joined with blank sections which can be fitting with sensors or emergency downlights.



General Information

Materials	Housing polycarbonate and powder coated steel
Installation Area	Internal

Inda

IND5F50ND5
IND5F50/DV



Optional Gear

Product Code	Description	Type
MWS-REC/DV	Recessed microwave Sensor, 1-10V dim output, remote required	Microwave Sensor
NTR03/ST	Nitro Emergency Downlight 3W Self-test White	Emergency Light
NTR03	Nitro Emergency Downlight 3W Manual test White	Emergency Light
MWS-SID/DV	M31 Side-Mount 1-10V microwave motion sensor MC054V RC	Microwave Sensor
MWS-SID	M30 Side-mount microwave motion ON/OFF sensor	Microwave Sensor
PIR-SID	P30 Exterior PIR Sensor Side-Mount with RMT-UNI control	PIR Sensor

Accessories

Product Code	Description	Type
IND-BLANK	Inda interlock blank section 228mm	Connector kit
IND5F-BLANK	Blank section for 5ft Inda batten	

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only

Overview

The slim backlight Inda batten is CCT switchable and 1-10V/0-10V dimmable. With multiple wattage, DALI dimming, side mounted sensors and integrated emergency options. If you want to keep the slim design on show, multiple fittings can be joined with blank sections which can be fitting with sensors or emergency downlights.



General Information

Materials	Housing polycarbonate and powder coated steel
Installation Area	Internal

Inda

IND5F50/DV/E IND5F50/DV/E

Inda slim backlight batten 5ft 28/50W CCT switch 1-10VDim EME

- Switchable wattage and CCT switchable (3000K/4000K/5000K)
- Emergency options available
- Optional plug-in PIR ON/OFF sensor compatible with Uni-Remote
- DALI-2 DT 6, DSI, switchDIM, corridor FUNCTION V2 option available
- 228mm blank section with knock out sections to fit in motion sensor and EME downlight
- 1-10 (0-10V) dimming
- 20mm conduit entry
- Included 2.0m drop suspension kit



Technical Summary

Product Code	IND5F50/DV/E
Conduit Entry 20mm	TRUE

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK

KosnicLightingUK



7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Overview

The slim backlight Inda batten is CCT switchable and 1-10V/0-10V dimmable. With multiple wattage, DALI dimming, side mounted sensors and integrated emergency options. If you want to keep the slim design on show, multiple fittings can be joined with blank sections which can be fitting with sensors or emergency downlights.



General Information

Materials	Housing polycarbonate and powder coated steel
Installation Area	Internal

Inda

IND5F50ND5E50/DV/E



Optional Gear

Product Code	Description	Type
MWS-REC/DV	Recessed microwave Sensor, 1-10V dim output, remote required	Microwave Sensor
NTR03/ST	Nitro Emergency Downlight 3W Self-test White	Emergency Light
NTR03	Nitro Emergency Downlight 3W Manual test White	Emergency Light
MWS-SID/DV	M31 Side-Mount 1-10V microwave motion sensor MC054V RC	Microwave Sensor
MWS-SID	M30 Side-mount microwave motion ON/OFF sensor	Microwave Sensor
PIR-SID	P30 Exterior PIR Sensor Side-Mount with RMT-UNI control	PIR Sensor

Accessories

Product Code	Description	Type
IND-BLANK	Inda interlock blank section 228mm	Connector kit
IND5F-BLANK	Blank section for 5ft Inda batten	

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

