



## Brick Light


LED IP65 stainless steel recessed brick light  
4.5W LED 6000K

### DESCRIPTION

A modern design that gives an instant cool white light. Ultra low energy consumption and prolonged lamp life.

### FEATURES

- Opal diffuser with optional stainless steel frame offering a soft, stylish lighting effect
- Hole cut out size - L: 228mm / D: 75mm / H: 98mm
- Cable gland included
- Integral driver



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	Stainless Steel
Application	Internal	Mounting Type	Recessed
Product Warranty	5 Years	Net Weight	0.54 kg
Energy Efficiency Class	E		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Construction Materials Line 2	Stainless steel frame	Dimensions - Height	105 mm
Dimensions - Width	233 mm	Dimensions - Depth	75 mm
IP Rating	IP65		

### PRODUCT INFORMATION

Wattage Combined	4.5W	CCT Combined	6000K
Luminaire Lumens Combined	285 lm	lm/W Combined	63 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7





IP65

Lighting Technology used	LED	Non-Directional or Directional	NDLS
Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	6,000
Chromaticity coordinates x	0.32	Chromaticity coordinates y	0.341
Peak Luminous Intensity (cd)	84 cd	Stroboscopic effect metric (SVM)	0
Flicker Metric (pst)	0	R9 colour rendering index	42
Survival factor @6000hrs	0.9	Spectrum report available	Yes
Displacement Factor	0.96	CCT1/WATT1: Rated Peak Intensity	84 cd





IP65

### PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
BRICKLED	Standard	4.5	6000 K	285 lm	63 lm/W

### PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	668 g
Pallet Layer Qty	96
Pallet Layers	4
Pallet Qty	384
MOM / OPQ	1 / 6

