

5 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Mulu

09063 MUL0105

Kosnic

Mulu Emergency Bulkhead 5W Manual test IP65 6500K White

- All legends included
- 20mm Conduit entry
- Maintained and non-maintained option
- IP65 and IK10 (vandal resistant) for internal & external uses.
- Dual entry push-wire terminal block for easy loop-in loop-out wiring
- BESA box fitting points



Overview

Mulu LED Emergency Exit Sign or Emergency Bulkhead Luminaire is a self-contained, multi-purpose, non-maintained or maintained 3-hour emergency luminaire solution. It can be used with or without the emergency exit graphics and is supplied with adaptable self-adhesive graphics for escape routes guidance.



General Information

IK Rating	IK10
IP Rating	IP65
Protection Rating	Class II
Installation Area	Internal and External
UEM/EME Protection	Class II

Compliance

LVD	EN 60598-1:2024, EN 60598-2-1:2021, EN 60598-2-22:2022, EN 62471:2008, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE, REACH

Technical Summary

Product Code	MUL0105
Lumens Output Maximum	160 lm
Emergency Luminous Flux	160 lm
Maintained Luminous Flux	160 lm
Weight	0.5Kg
Dimensions (L x W x D) (mm)	352x110x67
UEM/EME Battery Life	4 y
UEM/EME Input Voltage	220-240Vac 50/60Hz
UEM/EME Ambient Temperature Range	0°C to 40°C
UEM/EME Power Factor	0.58
Emergency Modes	Maintained or Non-maintained
UEM/EME Test Function	Manual
UEM/EME CCT	6,500 K
UEM/EME Input Power (Max)	5 W
UEM/EME Protection	Class II
UEM/EME Dimensions (L x W x D) (mm)	110x352x67
UEM/EME Emergency Operation Test	Manual
Beam Angle - Lumi (°)	120

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK

5 **5 Years**
Product Warranty
UK Only

2 **2 Years**
On-Site Warranty
Main-land UK Only

Overview

Mulu LED Emergency Exit Sign or Emergency Bulkhead Luminaire is a self-contained, multi-purpose, non-maintained or maintained 3-hour emergency luminaire solution. It can be used with or without the emergency exit graphics and is supplied with adaptable self-adhesive graphics for escape routes guidance.



General Information

IK Rating	IK10
IP Rating	IP65
Protection Rating	Class II
Installation Area	Internal and External
UEM/EME Protection	Class II

Mulu

09063 MUL0105



Accessories

Product Code	Description	Type
KBAT2600LI1	Li-ion Battery Pack, 2600mAh for self test versions of Manot, Mulu, Belum, Kalem, Nitro, Nitro surface, Doxa	Battery
KBAT2000LI1	Li-ion battery 3.7V 2000mAh for self test DD EME	Battery
BAT15NC3	Ni-cd battery SC1500mAh, 3.6V, 55° for MULU	Battery
BATC18LFP1	Battery LiFePO4 1800mAh, 3.2V	Battery

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

