

Skylineslim

Skyline Slim+ 150W Asymmetric LED Floodlight - 4000K

Part Code: 10978

The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

- Marine Grade Aluminium body
- Fully encapsulated IP65 TUV certified driver
- PIR Over-ride function
- Average 8M detection range for PIR Floods
- Separately tested IP65 PIR



5 Year
Guarantee



50,000
Life Hours



IK8
Rated



IP65
Rated

Skylineslim



Product Category Fittings / LED Floodlights

Application External Lighting

Product Warranty 5 Years

EAN 5013588109787

Commodity Code 9405423990

Country of Origin CN

Technical Specification

Wattage (W)	150
Equivalent Wattage (W)	250
Volts (V)	240
Colour Temperature (K)	4000
Lumen Output (lm)	19476
Lumens per Watt (lm/W)	130
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	1390mA
Energy Consumption (kWh/1000h)	150
Life Hours	50000
Switching Cycles	25000
IK Rating	IK08
IP Rating	IP65
Operating Temperature	-30°C to +35°C
Lumen Maintenance Ratio	80

Packaging Information

Minimum Order Quantity	1
Height (mm)	351
Width (mm)	302
Depth (mm)	60
Individual Product Weight (kg)	3.708
Single Box Weight (kg)	3.92359
Single Box Height (mm)	305
Single Box Width (mm)	70
Single Box Depth (mm)	359
Single Box Volume	0.00766
Outer Box Qty	2
Outer Box Barcode	1097800000002
Outer Box Weight (kg)	8.21587
Outer Box Height (mm)	310
Outer Box Width (mm)	148
Outer Box Depth (mm)	367
Outer Box Volume	0.01684
UNSPSC Code	39111626

skyline slim

Additional Information

Power Factor	>0.9
Windage	0.08m ²
LED Chip	Phillips
Flex	1m