

# Skylineslim

## Skyline Slim+ 30W LED Floodlight - 4000K

### Part Code: 10982

The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

- Marine Grade Aluminium body
- Fully encapsulated IP65 TUV certified driver
- 10/20/30/50W versions are genuine replacements for Halogen Floodlights
- 70/100/150/200W versions are genuine replacements for Metal Halide Floodlights
- Average 8M detection range for PIR Floods



**5 Year**  
Guarantee



**50,000**  
Life Hours



**IK8**  
Rated



**IP65**  
Rated

# Skylineslim



**Product Category** Fittings / LED Floodlights

**Application** External Lighting

**Product Warranty** 5 Years

**EAN** 5013588109824

**Commodity Code** 9405423990

**Country of Origin** CN

## Technical Specification

Wattage (W)	30
Equivalent Wattage (W)	240
Volts (V)	240
Colour Temperature (K)	4000
Lumen Output (lm)	4432
Lumens per Watt (lm/W)	148
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	305mA
Energy Consumption (kWh/1000h)	30
Life Hours	50000
Switching Cycles	25000
IK Rating	IK08
IP Rating	IP65
Operating Temperature	-30°C to +35°C
Lumen Maintenance Ratio	80

## Packaging Information

Minimum Order Quantity	1
Height (mm)	158
Width (mm)	136
Depth (mm)	34
Individual Product Weight (kg)	0.532
Single Box Weight (kg)	0.59519
Single Box Height (mm)	137
Single Box Width (mm)	56
Single Box Depth (mm)	157
Single Box Volume	0.0012
Outer Box Qty	12
Outer Box Barcode	1098200000012
Outer Box Weight (kg)	7.57683
Outer Box Height (mm)	353
Outer Box Width (mm)	280
Outer Box Depth (mm)	163
Outer Box Volume	0.01611
UNSPSC Code	39111626

# skyline slim

## Additional Information

Beam Angle	110°
Power Factor	>0.9
Windage	0.014m <sup>2</sup>
LED Chip	Phillips
Flex	1m