

Skylineslim

Skyline Slim+ 50W LED Asymmetric Floodlight - 4000K

Part Code: 10995

The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

- Marine Grade Aluminium body
- Fully encapsulated IP65 TUV certified driver
- 10/20/30/50W versions are genuine replacements for Halogen Floodlights
- 70/100/150/200W versions are genuine replacements for Metal Halide Floodlights
- Average 8M detection range for PIR Floods



5 Year
Guarantee



50,000
Life Hours



IK8
Rated



IP65
Rated

Skylineslim



Product Category Fittings / LED Floodlights

Application External Lighting

Product Warranty 5 Years

EAN 5013588109954

Commodity Code 9405423990

Country of Origin CN

Technical Specification

Wattage (W)	50
Equivalent Wattage (W)	400
Volts (V)	240
Colour Temperature (K)	4000
Lumen Output (lm)	6240
Lumens per Watt (lm/W)	125
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	510mA
Energy Consumption (kWh/1000h)	50
Life Hours	50000
Switching Cycles	25000
IK Rating	IK08
IP Rating	IP65
Operating Temperature	-30°C to +35°C
Lumen Maintenance Ratio	80

Packaging Information

Minimum Order Quantity	1
Height (mm)	200
Width (mm)	172
Depth (mm)	44
Individual Product Weight (kg)	1.39
Single Box Weight (kg)	1.51502
Single Box Height (mm)	232
Single Box Width (mm)	58
Single Box Depth (mm)	256
Single Box Volume	0.00344
Outer Box Qty	6
Outer Box Barcode	1099500000006
Outer Box Weight (kg)	9.55129
Outer Box Height (mm)	365
Outer Box Width (mm)	236
Outer Box Depth (mm)	262
Outer Box Volume	0.02257
UNSPSC Code	39111626

skyline slim

Additional Information

Beam Angle	110°
Power Factor	>0.9
Windage	0.044m ²
LED Chip	Phillips
Flex	1m