

## LED CCT Wallpack

### Muro 16/18/20/22W LED CCT Wallpack in Emergency

#### Part Code: 11351

Designed to be used where the aesthetics of the light fitting, along with a tough robust construction, is needed. The fittings are IP65 and IK8 compliant, supplied complete with an opal diffuser for even light distribution.

- Bat safe at 3000K
- Genuine replacement for 70W Metal Halide & Sodium
- High impact polycarbonate construction
- 68% energy saving



**3 Year**  
Guarantee



**1 Year**  
On-Site Warranty



**35,000**  
Life Hours



**IP65**  
Rated



## LED CCT Wallpack



**Product Category** Fittings / LED Wallpacks

**Application** External Lighting

**Product Warranty** 3 Years (1 Year On Site)

**EAN** 5013588113517

**Commodity Code** 9405423100

**Country of Origin** CN

### Technical Specification

Wattage (W)	16/18/20/22
Volts (V)	220/240
Colour Temperature (K)	3000/4000/6000
Lumen Output (lm)	16W = 1908 (3000K) - 2095 (4000K) - 1973 (6000K) / 18W = 2056 (3000K) - 2289 (4000K) - 2141 (6000K) / 20W = 2222 (3000K) - 2481 (4000K) - 2290 (6000K) / 22W = 2329 (3000K) - 2652 (4000K) - 2418 (6000K)
Lumens per Watt (lm/W)	106-131
Emergency Lumen Output (lm)	163
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	16W = 370mA / 18W = 418mA / 20W = 464mA / 22W = 510mA
Energy Consumption (kWh/1000h)	22
Life Hours	35000
Switching Cycles	30000
IK Rating	IK08
IP Rating	IP65
Operating Temperature	-30°C - +35°C
Emergency Wattage (W)	2
Lumen Maintenance Ratio	80

### Packaging Information

Minimum Order Quantity	1
Height (mm)	305
Width (mm)	255
Depth (mm)	100
Individual Product Weight (kg)	11
Single Box Weight (kg)	1.2
Single Box Height (mm)	310
Single Box Width (mm)	260
Single Box Depth (mm)	105
Single Box Volume	0.00846
Outer Box Qty	10
Outer Box Barcode	1135100000010
Outer Box Weight (kg)	13.5
Outer Box Height (mm)	650
Outer Box Width (mm)	550
Outer Box Depth (mm)	280
Outer Box Volume	0.1001
UNSPSC Code	39111612



## LED CCT Wallpack

Construction	
Primary Material	Polycarbonate

  

Electrical Information	
Electric Class	Class II

  

Installation Information	
Driver Integral?	Yes



## LED CCT Wallpack

Additional Information	
Beam Angle	113°
LED Chip	Samsung
Bat Safe	Yes - only at 3000K