

Skylinevirtus

Skyline Virtus 50/75/100W Wattage Switchable 30° Floodlight - 4000K

Part Code: 11482

The Skyline Virtus is a high specification floodlight, designed and engineered specifically to meet the requirements for sports lighting and to reduce light pollution levels. The Skyline Virtus is a high specification floodlight and is wattage switchable as standard.

- Wattage Switchable
- Perfect for sports, building facade's, landscape, security & car park lighting
- Aerodynamic, streamlined design for reduced windage
- Air pressure equalisation feature to eliminate capillary effect



7 Year
Guarantee



50,000
Life Hours



IP66
Rated



IK8
Rated



skylinevirtus



Product Category Fittings / LED Floodlights

Application Sports Lighting

Product Warranty 7 Years (2 Years On Site)

EAN 5013588114828

Commodity Code 9405920090

Country of Origin CN

Technical Specification

Wattage (W)	50/75/100
Equivalent Wattage (W)	250
Volts (V)	110/240
Colour Temperature (K)	4000
Lumen Output (lm)	7446 (50W) / 11981 (75W) / 15975 (100W)
Lumens per Watt (lm/W)	149-160
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	130mA
Energy Consumption (kWh/1000h)	100
Life Hours	50000
Switching Cycles	100000
IK Rating	IK08
IP Rating	IP66
Operating Temperature	-30°C to +35°C
Lumen Maintenance Ratio	80

Packaging Information

Minimum Order Quantity	1
Height (mm)	353
Width (mm)	287
Depth (mm)	65
Individual Product Weight (kg)	2.8
Single Box Weight (kg)	3.5
Single Box Height (mm)	375
Single Box Width (mm)	320
Single Box Depth (mm)	90
Single Box Volume	0.0108
UNSPSC Code	39111626

Skylinevirtus

Additional Information

Beam Angle	30°
Power Factor	>0.9
Windage	0.067m ²
LED Chip	Nichia GRT-V1
Flex	1.5m

Accessories

11581	360° Visor for the 50/75/100W Skyline Virtus LED Floodlight
11583	360° Visor for the 100/150/200W Skyline Virtus LED Floodlight
11585	360° Visor for the 150/225/300W Skyline Virtus LED Floodlight