

Skylinevirtus

Skyline Virtus 150/225/300W Wattage Switchable 30° Floodlight - 4000K

Part Code: 11484

The Skyline Virtus is a high specification floodlight, designed and engineered specifically to meet the requirements for sports lighting and to reduce light pollution levels. The Skyline Virtus is a high specification floodlight and is wattage switchable as standard.

- Wattage Switchable
- Perfect for sports, building facade's, landscape, security & car park lighting
- Aerodynamic, streamlined design for reduced windage
- Air pressure equalisation feature to eliminate capillary effect



7 Year
Guarantee



50,000
Life Hours



IP66
Rated



IK8
Rated



skylinevirtus



Product Category	Fittings / LED Floodlights
Application	Sports Lighting
Product Warranty	7 Years (2 Years On Site)
EAN	5013588114842
Commodity Code	9405423990
Country of Origin	CN

Technical Specification

Wattage (W)	150/225/300
Equivalent Wattage (W)	750
Volts (V)	110/240
Colour Temperature (K)	4000
Lumen Output (lm)	23417 (150W) / 35856 (225W) / 47808 (300W)
Lumens per Watt (lm/W)	156-159
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	132mA
Energy Consumption (kWh/1000h)	300
Life Hours	50000
Switching Cycles	100000
IK Rating	IK08
IP Rating	IP66
Operating Temperature	-30°C to +35°C
Lumen Maintenance Ratio	80

Packaging Information

Minimum Order Quantity	1
Height (mm)	495
Width (mm)	419
Depth (mm)	75
Individual Product Weight (kg)	6.4
Single Box Weight (kg)	7.4
Single Box Height (mm)	525
Single Box Width (mm)	450
Single Box Depth (mm)	115
Single Box Volume	0,02716875
UNSPSC Code	39111626

Skylinevirtus

Additional Information

Beam Angle	30°
Power Factor	>0.9
Windage	0.144m ²
LED Chip	Nichia GRT-V1
Flex	1.5m

Accessories

11581	360° Visor for the 50/75/100W Skyline Virtus LED Floodlight
11583	360° Visor for the 100/150/200W Skyline Virtus LED Floodlight
11585	360° Visor for the 150/225/300W Skyline Virtus LED Floodlight