



LED CCT Asymmetric Wallpack

Lumo 13/16/18/20/25W LED CCT Asymmetric Wallpack

Part Code: 11500

Designed to be used where the aesthetics of the light fitting, along with a tough robust construction is needed. The fittings are IP66 and IK8 compliant, supplied complete with an opal diffuser for even light distribution. Available in Standard / Photocell / Emergency / Emergency Photocell versions.

- CCT 3/4/6000K
- Genuine replacement for 50W Metal Halide & Sodium
- TUV Certified Driver
- High impact polycarbonate lens
- 50% energy saving



7 Year
Guarantee



50,000
Life Hours



2 Year
On-Site Warranty



IP66
Rated



LED CCT Asymmetric Wallpack



Product Category	Fittings / LED Wallpacks
Application	External Lighting
Product Warranty	7 Years
EAN	5013588115009
Commodity Code	9405423100
Country of Origin	CN

Technical Specification

Wattage (W)	13/16/18/20/25
Equivalent Wattage (W)	50
Volts (V)	220/240
Colour Temperature (K)	3000/4000/6000
Lumen Output (lm)	13W = 1669 (3000K) / 1684 (4000K) / 1603 (6000K) - 16W = 2078 (3000K) / 2207 (4000K) / 2153 (6000K) - 18W = 2341 (3000K) / 2500 (4000K) / 2427 (6000K) - 20W = 2538 (3000K) / 2720 (4000K) / 2632 (6000K) - 25W = 3080 (3000K) / 3341 (4000K) / 3190 (6000K)
Lumens per Watt (lm/W)	123-133
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	78mA
Energy Consumption (kWh/1000h)	25
Life Hours	50000
Switching Cycles	50000
IK Rating	IK08
IP Rating	IP66

Packaging Information

Minimum Order Quantity	1
Height (mm)	238
Width (mm)	212
Depth (mm)	138
Individual Product Weight (kg)	1.9
Single Box Weight (kg)	2.2
Single Box Height (mm)	260
Single Box Width (mm)	235
Single Box Depth (mm)	160
Single Box Volume	0.00978
Inner Box Barcode	5013588115009
Outer Box Qty	4
Outer Box Barcode	1150000000004
Outer Box Height (mm)	500
Outer Box Width (mm)	355
Outer Box Depth (mm)	280
Outer Box Volume	0.0497
UNSPSC Code	39111612