

# LUMO2

## Lumo 2 CCT 14/17/21/24W LED Asymmetric Wallpack

**Part Code: 70120**

The Lumo 2 Wallpack is designed to be used where the aesthetics of the light fitting, along with a tough robust construction is needed.

- CCT 3/4/6000K
- Bat safe at 3000K
- Asymmetric Light Distribution
- Wattage Switchable



**3**

Colour Temperatures



**50,000**

Life Hours



**2 Year**

On-Site Warranty



**7 Year**

Guarantee



# LUMO2



**Product Category** Fittings / LED Wallpacks

**Application** External Lighting

**Product Warranty** 7 Years (2 Years On Site)

**EAN** 5013588701202

**Commodity Code** 9405423100

**Country of Origin** CN

## Technical Specification

Wattage (W)	14/17/21/24
Equivalent Wattage (W)	70
Volts (V)	220/240
Colour Temperature (K)	3000/4000/6000
Lumen Output (lm)	14W = 1781 (3000K) - 1920 (4000K) - 1801 (6000K) / 17W = 2141 (3000K) - 2316 (4000K) - 2165 (6000K) / 21W = 2611 (3000K) - 2821 (4000K) - 2632 (6000K) / 24W = 2932 (3000K) - 3241 (4000K) - 2943 (6000K)
Lumens per Watt (lm/W)	122-137
Candelas	1300-2400
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	350mA
Energy Consumption (kWh/1000h)	24
Life Hours	50000
Switching Cycles	50000
IP Rating	IP65

## Packaging Information

Minimum Order Quantity	1
Height (mm)	217
Width (mm)	309
Depth (mm)	162
Individual Product Weight (kg)	1.15
Single Box Weight (kg)	1.3
Single Box Height (mm)	175
Single Box Width (mm)	320
Single Box Depth (mm)	230
Single Box Volume	0.01288
Outer Box Qty	10
Outer Box Barcode	7012000000010
Outer Box Weight (kg)	14.5
Outer Box Height (mm)	335
Outer Box Width (mm)	990
Outer Box Depth (mm)	495
Outer Box Volume	0.16416675
UNSPSC Code	39111612

The LUMO2 logo consists of a black circle containing a white stylized 'L' on the left, followed by the word "LUMO2" in a bold, black, sans-serif font.

Additional Information	
Beam Angle	120°
Bat Safe	Yes - only at 3000K

Accessories	
70129	Emergency Pack for Lumo 2 CCT LED Wallpack
11505	Emergency Pack for the Lumo 13/16/18/20/25W CCT Asymmetric Wallpack