

LUMO2

Lumo 2 CCT 14/17/21/24W LED Symmetric Wallpack in Emergency with Photocell

Part Code: 70127

The Lumo 2 Wallpack is designed to be used where the aesthetics of the light fitting, along with a tough robust construction is needed.

- CCT 3/4/6000K
- Bat safe at 3000K
- Symmetric Light Distribution
- Wattage Switchable



3

Colour Temperatures



50,000

Life Hours



2 Year

On-Site Warranty



7 Year

Guarantee



LUMMO2



Product Category Fittings / LED Wallpacks

Application External Lighting

Product Warranty 7 Years (2 Years On Site)

EAN 5013588701271

Commodity Code 9405423100

Country of Origin CN

Technical Specification

Wattage (W)	14/17/21/24
Equivalent Wattage (W)	64
Volts (V)	220/240
Colour Temperature (K)	3000/4000/6000
Lumen Output (lm)	14W = 1702 (3000K) - 1872 (4000K) - 1712 (6000K) / 17W = 2037 (3000K) - 2212 (4000K) - 2043 (6000K) / 21W = 2481 (3000K) - 2683 (4000K) - 2502 (6000K) / 24W = 2821 (3000K) - 3071 (4000K) - 2862 (6000K)
Lumens per Watt (lm/W)	118-134
Emergency Lumen Output (lm)	128 (3000K) / 125 (4000K) / 127 (6000K)
Candelas	1300-2400
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	350mA
Energy Consumption (kWh/1000h)	24
Life Hours	50000
Switching Cycles	50000
IP Rating	IP65
Emergency Wattage (W)	1.5

Packaging Information

Minimum Order Quantity	1
Height (mm)	217
Width (mm)	309
Depth (mm)	162
Individual Product Weight (kg)	1.15
Single Box Weight (kg)	1.3
Single Box Height (mm)	175
Single Box Width (mm)	320
Single Box Depth (mm)	230
Single Box Volume	0.01288
Outer Box Qty	10
Outer Box Barcode	7012700000010
Outer Box Weight (kg)	14.5
Outer Box Height (mm)	335
Outer Box Width (mm)	990
Outer Box Depth (mm)	495
Outer Box Volume	0.16416675
UNSPSC Code	39111612

The logo for LUMO2, featuring a stylized "L" inside a circle followed by "UMO2" in a bold, sans-serif font.

Additional Information	
Beam Angle	120°
Bat Safe	Yes - only at 3000K

Accessories	
70129	Emergency Pack for Lumo 2 CCT LED Wallpack
11505	Emergency Pack for the Lumo 13/16/18/20/25W CCT Asymmetric Wallpack