

# Skylinevirtus

## Skyline Virtus 100/150/200W Wattage Switchable Asymmetric Floodlight - 2700K

**Part Code: 70302**

The Skyline Virtus is a high specification floodlight, designed and engineered specifically to meet the requirements for sports lighting and to reduce light pollution levels. The Skyline Virtus is a high specification floodlight and is wattage switchable as standard.

- Wattage Switchable
- Perfect for sports, building facade's, landscape, security & car park lighting
- Aerodynamic, streamlined design for reduced windage
- Air pressure equalisation feature to eliminate capillary effect



**7 Year**  
Guarantee



**50,000**  
Life Hours



**IP66**  
Rated



**IK8**  
Rated



# skylinevirtus



**Product Category** Fittings / LED Floodlights

**Application** Sports Lighting

**Product Warranty** 7 Years (2 Years On Site)

**EAN** 5013588703022

**Commodity Code** 9405423990

**Country of Origin** CN

## Technical Specification

Wattage (W)	100/150/200
Equivalent Wattage (W)	250-500
Volts (V)	110/240
Colour Temperature (K)	2700
Lumen Output (lm)	14461 (100W) / 20971 (150W) / 27424 (200W)
Lumens per Watt (lm/W)	137-145
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	139mA
Energy Consumption (kWh/1000h)	200
Life Hours	50000
Switching Cycles	100000
IK Rating	IK08
IP Rating	IP66
Operating Temperature	-30°C to +35°C
Lumen Maintenance Ratio	80

## Packaging Information

Minimum Order Quantity	1
Height (mm)	447
Width (mm)	359
Depth (mm)	75
Individual Product Weight (kg)	5.2
Single Box Weight (kg)	6.2
Single Box Height (mm)	480
Single Box Width (mm)	390
Single Box Depth (mm)	115
Single Box Volume	0.021528
UNSPSC Code	39111626

# Skylinevirtus

## Additional Information

Power Factor	>0.9
Windage	0.112m <sup>2</sup>
LED Chip	Nichia GRT-V1
Flex	1.5m

## Accessories

11581	360° Visor for the 50/75/100W Skyline Virtus LED Floodlight
11583	360° Visor for the 100/150/200W Skyline Virtus LED Floodlight
11585	360° Visor for the 150/225/300W Skyline Virtus LED Floodlight