

Skylinevirtus

Skyline Virtus 150/225/300W Wattage Switchable Symmetric Floodlight - 5700K

Part Code: 70311

The Skyline Virtus is a high specification floodlight, designed and engineered specifically to meet the requirements for sports lighting and to reduce light pollution levels. The Skyline Virtus is a high specification floodlight and is wattage switchable as standard.

- Wattage Switchable
- Perfect for sports, building facade's, landscape, security & car park lighting
- Aerodynamic, streamlined design for reduced windage
- Air pressure equalisation feature to eliminate capillary effect



7 Year
Guarantee



50,000
Life Hours



IP66
Rated



IK8
Rated



skylinevirtus



Product Category Fittings / LED Floodlights

Application Sports Lighting

Product Warranty 7 Years (2 Years On Site)

EAN 5013588703114

Commodity Code 9405423990

Country of Origin CN

Technical Specification

Wattage (W)	150/225/300
Equivalent Wattage (W)	750
Volts (V)	110/240
Colour Temperature (K)	5700
Lumen Output (lm)	22771 (150W) / 35018 (225W) / 46690 (300W)
Lumens per Watt (lm/W)	152-156
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	132mA
Energy Consumption (kWh/1000h)	300
Life Hours	50000
Switching Cycles	100000
IK Rating	IK08
IP Rating	IP66
Operating Temperature	-30°C to +35°C
Lumen Maintenance Ratio	80

Packaging Information

Minimum Order Quantity	1
Height (mm)	495
Width (mm)	419
Depth (mm)	75
Individual Product Weight (kg)	6.4
Single Box Weight (kg)	7.4
Single Box Height (mm)	525
Single Box Width (mm)	450
Single Box Depth (mm)	115
Single Box Volume	0,02716875
UNSPSC Code	39111626

Skylinevirtus

Additional Information

Power Factor	>0.9
Windage	0.144m ²
LED Chip	Nichia GRT-V1
Flex	1.5m

Accessories

11581	360° Visor for the 50/75/100W Skyline Virtus LED Floodlight
11583	360° Visor for the 100/150/200W Skyline Virtus LED Floodlight
11585	360° Visor for the 150/225/300W Skyline Virtus LED Floodlight