

Illuminaversa

Illumina Versa 60/80/100W LED CCT High Bay - Beam Angle Selectable with Zhaga Receptacle

Part Code: 70420

The Illumina Versa is a complete, all-in-one high bay lighting solution. It features selectable wattage, colour temperature, and beam angle, along with a Zhaga receptacle for added flexibility and future-ready connectivity.

- A versatile product designed to meet all customer needs
- Selectable beam angles
- 1-10V dimmable as standard
- Smart controls enables through Zhaga 18 socket
- Wattage switchable



70,000
Life Hours



Beam Angle
Selectable



Colour
Selectable



Wattage
Selectable

Olluminaversa



Product Category Fittings / LED Warehouse Lighting

Application Warehouse Lighting

Product Warranty 8 Years (2 Years On Site)

EAN 5063695004673

Commodity Code 9405423990

Country of Origin CN

Technical Specification

Wattage (W)	60/80/100
Volts (V)	220/240
Colour Temperature (K)	3000/4000/5000
Lumen Output (lm)	60W = 8967 (3000K) / 9801 (4000K) / 9369 (5000K) - 80W = 11830 (3000K) / 13052 (4000K) / 12387 (5000K) - 100W = 13409 (3000K) / 15756 (4000K) / 14180 (5000K) - at 120°
Lumens per Watt (lm/W)	149-163 - at 120°
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	67mA
Energy Consumption (kWh/1000h)	100
Life Hours	70000
Switching Cycles	100,000
IK Rating	IK08
IP Rating	IP65
Operating Temperature	-20°C - +35°C
Lumen Maintenance Ratio	L80 B10

Packaging Information

Minimum Order Quantity	1
Height (mm)	174
Diameter (mm)	251
Individual Product Weight (kg)	1.94
Single Box Weight (kg)	2.31
Single Box Height (mm)	270
Single Box Width (mm)	270
Single Box Depth (mm)	185
Single Box Volume	0.0134865
UNSPSC Code	39111538

Olluminaversa

Construction

Driver Manufacturer	Sosen
Primary Material	Die-cast Aluminium
Diffuser Material	Polycarbonate

Electrical Information

Electric Class	Class I
Surge Protection	6kV

Installation Information

Driver Integral?	Yes
------------------	-----

illuminaversa

Additional Information

Beam Angle	60° / 90° / 120°
Power Factor	>0.9
LED Chip	SMD 2835
Standard Deviation Colour Matching	<5-step MacAdam Ellipse (<3 at 3000K)
Flex	1.5m