

skylinevirtus

Skyline Virtus CCT 50/75/100W LED Asymmetric Floodlight - In-Built Photocell with On/Off

Part Code: 70470

The Skyline Virtus CCT LED floodlight is both wattage and colour switchable, offering versatility as well as performance.

- Bat safe at 3000K
- C5-M Marine Grade treated construction suitable for coastal areas & harsh environments
- Supplied with pre-wired 1.5m cable
- Suitable for site lighting
- Suitable for sports lighting, façade lighting, area lighting & open car parks



8 Year
Guarantee



100,000
Life Hours



IP66
Rated



IK08
Rated



skylinevirtus



Product Category Fittings / LED Floodlights

Application LED Floodlight

Product Warranty 8 Years (2 Years On Site)

EAN 5063695041401

Commodity Code 9405423990

Country of Origin CN

Technical Specification

Wattage (W)	50/75/100
Volts (V)	110/240
Colour Temperature (K)	3000/4000/5000
Lumen Output (lm)	50W = 8000 (3000K) / 8600 (4000K) / 8400 (5000K) - 75W = 11550 (3000K) / 12750 (4000K) / 12000 (5000K) - 100W = 15000 (3000K) / 16800 (4000K) / 15800 (5000K)
Lumens per Watt (lm/W)	150-172
CRI (ra)	70
Frequency (Hz)	50/60
LED Drive Current	59mA
Energy Consumption (kWh/1000h)	100
Life Hours	100000
Switching Cycles	100000
IK Rating	IK08
IP Rating	IP66
Operating Temperature	-30°C - +45°C

Packaging Information

Minimum Order Quantity	1
Height (mm)	358
Width (mm)	277
Length (mm)	53
Individual Product Weight (kg)	2.7
Single Box Weight (kg)	3.3
Single Box Height (mm)	390
Single Box Width (mm)	315
Single Box Depth (mm)	85
Single Box Volume	0.01044225
UNSPSC Code	39111612

skylinevirtus

Construction

Driver Manufacturer	Sosen
Primary Material	Aluminium

Electrical Information

Electric Class	Class I
Surge Protection	10KV

skylinevirtus

Additional Information

Power Factor	>0.95
Windage	0.09m ² at 90°
LED Chip	SMD 2835
Standard Deviation Colour Matching	5-step MacAdam ellipse
Bat Safe	Yes - only at 3000K
Flex	1.5m