

# skylinevirtus

## Skyline Virtus CCT 150/225/300W LED Symmetric Floodlight - In-Built Photocell with On/Off

**Part Code: 70475**

The Skyline Virtus CCT LED floodlight is both wattage and colour switchable, offering versatility as well as performance.

- Bat safe at 3000K
- C5-M Marine Grade treated construction suitable for coastal areas & harsh environments
- Supplied with pre-wired 1.5m cable
- Suitable for site lighting
- Suitable for sports lighting, façade lighting, area lighting & open car parks



**8 Year**  
Guarantee



**100,000**  
Life Hours



**IP66**  
Rated



**IK08**  
Rated



# skylinevirtus



**Product Category** Fittings / LED Floodlights

**Application** LED Floodlight

**Product Warranty** 8 Years (2 Years On Site)

**EAN** 5063695041456

**Commodity Code** 9405423990

**Country of Origin** CN

## Technical Specification

Wattage (W)	150/225/300
Volts (V)	110/240
Colour Temperature (K)	3000/4000/5000
Lumen Output (lm)	150W = 24900 (3000K) / 27750 (4000K) / 26250 (5000K) - 225W = 33975 (3000K) / 39375 (4000K) / 35775 (5000K) - 300W = 43500 (3000K) / 51300 (4000K) / 46500 (5000K)
Lumens per Watt (lm/W)	145-185
CRI (ra)	70
Frequency (Hz)	50/60
LED Drive Current	78mA
Energy Consumption (kWh/1000h)	300
Life Hours	100000
Switching Cycles	100000
IK Rating	IK08
IP Rating	IP66
Operating Temperature	-30°C - +45°C

## Packaging Information

Minimum Order Quantity	1
Height (mm)	443
Width (mm)	363
Length (mm)	53
Individual Product Weight (kg)	4.9
Single Box Weight (kg)	6
Single Box Height (mm)	480
Single Box Width (mm)	405
Single Box Depth (mm)	85
Single Box Volume	0.016524
UNSPSC Code	39111612

# skylinevirtus

## Construction

Driver Manufacturer	Sosen
Primary Material	Aluminium

## Electrical Information

Electric Class	Class I
Surge Protection	10KV

# skylinevirtus

## Additional Information

Beam Angle	60°
Power Factor	>0.95
Windage	0.14m <sup>2</sup> at 90°
LED Chip	SMD 2835
Standard Deviation Colour Matching	5-step MacAdam ellipse
Bat Safe	Yes - only at 3000K
Flex	1.5m