

skylineomni

Skyline Omni 20W LED Floodlight - 3CCT

Part Code: 72031

The Skyline Omni is a CCT Floodlight with Wattage Switchability in higher wattage models, featuring a compact design, adjustable bracket and tempered glass cover.

- Bat safe at 3000K
- Replaceable Slim Front Frame
- Versatile Angled Adjustable Bracket
- Die-cast Aluminium Housing
- Pre-wired with 1m Lead



7 Year
Guarantee



50,000
Life Hours



80
CRI



Colour
Switchable



skylineomni



Product Category	Fittings / LED Floodlights
Application	LED Floodlight
Product Warranty	7 Years
EAN	5063695003270
Commodity Code	9405423990
Country of Origin	CN

Technical Specification

Wattage (W)	20
Volts (V)	220/240
Colour Temperature (K)	3000/4000/5000
Lumen Output (lm)	2185 (3000K) / 2469 (4000K) / 2357 (5000K)
Lumens per Watt (lm/W)	109-123
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	130mA at 230V
Energy Consumption (kWh/1000h)	20
Life Hours	50000
Switching Cycles	25000
IK Rating	IK07
IP Rating	IP65
Operating Temperature	-20°C - +40°C

Packaging Information

Minimum Order Quantity	1
Height (mm)	220
Width (mm)	100
Depth (mm)	38
Individual Product Weight (kg)	0.385
Single Box Weight (kg)	0.454
Single Box Height (mm)	104
Single Box Width (mm)	60
Single Box Depth (mm)	197
Single Box Volume	0.00122928
Outer Box Qty	24
Outer Box Weight (kg)	11.61
Outer Box Height (mm)	440
Outer Box Width (mm)	390
Outer Box Depth (mm)	228
Outer Box Volume	0.0391248
UNSPSC Code	39111704

Additional Information	
Beam Angle	110°
Power Factor	0.6
Windage	0.01m ²
Bat Safe	Yes - only at 3000K
Flex	1m

Beam Angle	110°
Power Factor	0.6
Windage	0.01m ²
Bat Safe	Yes - only at 3000K
Flex	1m