

Skyline Omni 15/30W Wattage Selectable LED Floodlight - 3CCT

Part Code: 72032

The Skyline Omni is a CCT Floodlight with Wattage Switchability in higher wattage models, featuring a compact design, adjustable bracket and tempered glass cover.

- Bat safe at 3000K
- Replaceable Slim Front Frame
- Versatile Angled Adjustable Bracket
- Die-cast Aluminium Housing
- Pre-wired with 1m Lead



7 Year
Guarantee



50,000
Life Hours



80
CRI



Colour
Switchable



skylineomni



Product Category Fittings / LED Floodlights

Application LED Floodlight

Product Warranty 7 Years

EAN 5063695003287

Commodity Code 9405423990

Country of Origin CN

Technical Specification

Wattage (W)	15/30
Volts (V)	220/240
Colour Temperature (K)	3000/4000/5000
Lumen Output (lm)	15W = 1592 (3000K) / 1799 (4000K) / 1718 (5000K) - 30W = 3185 (3000K) / 3599 (4000K) / 3437 (5000K)
Lumens per Watt (lm/W)	106-120
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	130mA at 230V
Energy Consumption (kWh/1000h)	30
Life Hours	50000
Switching Cycles	25000
IK Rating	IK07
IP Rating	IP65
Operating Temperature	-20°C - +40°C

Packaging Information

Minimum Order Quantity	1
Height (mm)	257
Width (mm)	135
Depth (mm)	38
Individual Product Weight (kg)	0.585
Single Box Weight (kg)	0.665
Single Box Height (mm)	139
Single Box Width (mm)	60
Single Box Depth (mm)	202
Single Box Volume	0.00168468
Outer Box Qty	24
Outer Box Weight (kg)	16.88
Outer Box Height (mm)	580
Outer Box Width (mm)	390
Outer Box Depth (mm)	233
Outer Box Volume	0.0527046
UNSPSC Code	39111704

Additional Information	
Beam Angle	110°
Power Factor	0.9
Windage	0.0185m ²
Bat Safe	Yes - only at 3000K
Flex	1m

Beam Angle	110°
Power Factor	0.9
Windage	0.0185m ²
Bat Safe	Yes - only at 3000K
Flex	1m