

Skyline Omni 30/50W Wattage Switchable LED Floodlight - 3CCT

Part Code: 72033

The Skyline Omni is a CCT Floodlight with Wattage Switchability in higher wattage models, featuring a compact design, adjustable bracket and tempered glass cover.

- Bat safe at 3000K
- Replaceable Slim Front Frame
- Versatile Angled Adjustable Bracket
- Die-cast Aluminium Housing
- Pre-wired with 1m Lead



7 Year
Guarantee



50,000
Life Hours



80
CRI



Colour
Switchable



skylineomni



Product Category	Fittings / LED Floodlights
Application	LED Floodlight
Product Warranty	7 Years
EAN	5063695003294
Commodity Code	9405423990
Country of Origin	CN

Technical Specification

Wattage (W)	30/50
Volts (V)	220/240
Colour Temperature (K)	3000/4000/5000
Lumen Output (lm)	30W = 3282 (3000K) / 3709 (4000K) / 3541 (5000K) - 50W = 5470 (3000K) / 6181 (4000K) / 5902 (5000K)
Lumens per Watt (lm/W)	109-124
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	220mA at 230V
Energy Consumption (kWh/1000h)	50
Life Hours	50000
Switching Cycles	25000
IK Rating	IK07
IP Rating	IP65
Operating Temperature	-20°C - +40°C

Packaging Information

Minimum Order Quantity	1
Height (mm)	298
Width (mm)	168
Depth (mm)	39
Individual Product Weight (kg)	0.85
Single Box Weight (kg)	0.95
Single Box Height (mm)	172
Single Box Width (mm)	60
Single Box Depth (mm)	216
Single Box Volume	0.00222912
Outer Box Qty	18
Outer Box Weight (kg)	17.92
Outer Box Height (mm)	537
Outer Box Width (mm)	390
Outer Box Depth (mm)	247
Outer Box Volume	0.05172921
UNSPSC Code	39111704

Additional Information	
Beam Angle	110°
Power Factor	0.9
Windage	0.03m ²
Bat Safe	Yes - only at 3000K
Flex	1m

Beam Angle	110°
Power Factor	0.9
Windage	0.03m ²
Bat Safe	Yes - only at 3000K
Flex	1m