

skylineomni

Skyline Omni 50/80/100W Wattage Switchable LED Floodlight - Symmetric - 3CCT

Part Code: 72035

The Skyline Omni is a CCT Floodlight with Wattage Switchability in higher wattage models, featuring a compact design, adjustable bracket and tempered glass cover.

- Bat safe at 3000K
- Replaceable Slim Front Frame
- Versatile Angled Adjustable Bracket
- Die-cast Aluminium Housing
- Pre-wired with 1m Lead



7 Year
Guarantee



50,000
Life Hours



80
CRI



Colour
Switchable



skylineomni



Product Category Fittings / LED Floodlights

Application LED Floodlight

Product Warranty 7 Years

EAN 5063695003317

Commodity Code 9405423990

Country of Origin CN

Technical Specification

Wattage (W)	50/80/100
Volts (V)	220/240
Colour Temperature (K)	3000/4000/5000
Lumen Output (lm)	50W = 7005 (3000K) / 8194 (4000K) / 7578 (5000K) - 80W = 11208 (3000K) / 13110 (4000K) / 12125 (5000K) - 100W = 14010 (3000K) / 16387 (4000K) / 15156 (5000K)
Lumens per Watt (lm/W)	140-164
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	490mA at 230V
Energy Consumption (kWh/1000h)	100
Life Hours	50000
Switching Cycles	25000
IK Rating	IK08
IP Rating	IP65
Operating Temperature	-40°C - +45°C

Packaging Information

Minimum Order Quantity	1
Height (mm)	405
Width (mm)	293
Depth (mm)	65
Individual Product Weight (kg)	3.325
Single Box Weight (kg)	3.505
Single Box Height (mm)	309
Single Box Width (mm)	65
Single Box Depth (mm)	399
Single Box Volume	0.008013915
Outer Box Qty	2
Outer Box Weight (kg)	7.43
Outer Box Height (mm)	327
Outer Box Width (mm)	151
Outer Box Depth (mm)	459
Outer Box Volume	0.022664043
UNSPSC Code	39111704

Additional Information	
Beam Angle	110°
Power Factor	0.9
Windage	0.082m ²
Bat Safe	Yes - only at 3000K
Flex	1.5m

Beam Angle	110°
Power Factor	0.9
Windage	0.082m ²
Bat Safe	Yes - only at 3000K
Flex	1.5m