

Skylineomni

Skyline Omni 100/120/150W Wattage Switchable LED Floodlight - Asymmetric - 3CCT

Part Code: 72041

The Skyline Omni is a CCT Floodlight with Wattage Switchability in higher wattage models, featuring a compact design, adjustable bracket and tempered glass cover.

- Bat safe at 3000K
- Replaceable Slim Front Frame
- Versatile Angled Adjustable Bracket
- Die-cast Aluminium Housing
- Pre-wired with 1m Lead



7 Year
Guarantee



50,000
Life Hours



80
CRI



Colour
Switchable



skylineomni



Product Category Fittings / LED Floodlights

Application LED Floodlight

Product Warranty 7 Years

EAN 5063695003379

Commodity Code 9405423990

Country of Origin CN

Technical Specification

Wattage (W)	100/120/150
Volts (V)	220/240
Colour Temperature (K)	3000/4000/5000
Lumen Output (lm)	100W = 13841 (3000K) / 15737 (4000K) / 14120 (5000K) - 120W = 16610 (3000K) / 18884 (4000K) / 16944 (5000K) - 150W = 20763 (3000K) / 23605 (4000K) / 21180 (5000K)
Lumens per Watt (lm/W)	138-157
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	740mA at 230V
Energy Consumption (kWh/1000h)	150
Life Hours	50000
Switching Cycles	25000
IK Rating	IK08
IP Rating	IP65
Operating Temperature	-40°C - +45°C

Packaging Information

Minimum Order Quantity	1
Height (mm)	482
Width (mm)	373
Depth (mm)	69
Individual Product Weight (kg)	5.225
Single Box Weight (kg)	5.495
Single Box Height (mm)	389
Single Box Width (mm)	73
Single Box Depth (mm)	482
Single Box Volume	0.013687354
Outer Box Qty	2
Outer Box Weight (kg)	11.55
Outer Box Height (mm)	407
Outer Box Width (mm)	167
Outer Box Depth (mm)	542
Outer Box Volume	0.0356839198
UNSPSC Code	39111704

Additional Information	
Power Factor	0.9
Windage	0.133m ²
Bat Safe	Yes - only at 3000K
Flex	1.5m