

## Skylineomni

### Skyline Omni 200/250/300W Wattage Switchable LED Floodlight - Symmetric - Loop In Loop Out - 3CCT

**Part Code: 72045**

The Skyline Omni is a CCT Floodlight with Wattage Switchability in higher wattage models, featuring a compact design, adjustable bracket and tempered glass cover.

- Bat safe at 3000K
- Precise light distribution - advanced refractive optics with built in reflector
- High durability - 6mm tempered glass and IK08 rating
- Adjustable angled bracket with high strength
- Ease of installation - loop-in loop-out facility



**7 Year**  
Guarantee



**50,000**  
Life Hours



**80**  
CRI



**Colour**  
Switchable



# skylineomni



**Product Category** Fittings / LED Floodlights

**Application** LED Floodlight

**Product Warranty** 7 Years

**EAN** 5063695003416

**Commodity Code** 9405423990

**Country of Origin** CN

## Technical Specification

Wattage (W)	200/250/300
Volts (V)	220/240
Colour Temperature (K)	3000/4000/5000
Lumen Output (lm)	200W = 27031 (3000K) / 32518 (4000K) / 29476 (5000K) - 250W = 33789 (3000K) / 40648 (4000K) / 36845 (5000K) - 300W = 40547 (3000K) / 48777 (4000K) / 44214 (5000K)
Lumens per Watt (lm/W)	135-163
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	1470mA at 230V
Energy Consumption (kWh/1000h)	300
Life Hours	50000
Switching Cycles	25000
IK Rating	IK08
IP Rating	IP66
Operating Temperature	-40°C - +45°C

## Packaging Information

Minimum Order Quantity	1
Height (mm)	515
Width (mm)	440
Depth (mm)	77
Individual Product Weight (kg)	9.6
Single Box Weight (kg)	9.71
Single Box Height (mm)	536
Single Box Width (mm)	494
Single Box Depth (mm)	85
Single Box Volume	0.02250664
UNSPSC Code	39111704

Additional Information	
Power Factor	0.9
Windage	0.133m <sup>2</sup>
Bat Safe	Yes - only at 3000K
Flex	1.5m