

## skylineomni

### Skyline Omni 100/120/150W Wattage Switchable LED Floodlight with Photocell Switch - Symmetric - 3CCT

**Part Code: 72048**

The Skyline Omni is a CCT Floodlight with Wattage Switchability in higher wattage models, featuring a compact design, adjustable bracket and tempered glass cover.

- Bat safe at 3000K
- Replaceable Slim Front Frame
- Versatile Angled Adjustable Bracket
- Die-cast Aluminium Housing
- Pre-wired with 1m Lead



**7 Year**  
Guarantee



**50,000**  
Life Hours



**80**  
CRI



**Colour**  
Switchable





**Product Category** Fittings / LED Floodlights

**Application** LED Floodlight

**Product Warranty** 7 Years

**EAN** 5063695005038

**Commodity Code** 9405423990

**Country of Origin** CN

### Technical Specification

Wattage (W)	100/120/150
Volts (V)	220/240
Colour Temperature (K)	3000/4000/5000
Lumen Output (lm)	100W = 14571 (3000K) / 17043 (4000K) / 15763 (5000K) - 120W = 17485 (3000K) / 20452 (4000K) / 18915 (5000K) - 150W = 21857 (3000K) / 25565 (4000K) / 23644 (5000K)
Lumens per Watt (lm/W)	146-170
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	740mA at 230V
Energy Consumption (kWh/1000h)	150
Life Hours	50000
Switching Cycles	25000
IK Rating	IK08
IP Rating	IP65
Operating Temperature	-40°C - +45°C

### Packaging Information

Minimum Order Quantity	1
Height (mm)	482
Width (mm)	373
Depth (mm)	69
Individual Product Weight (kg)	5.225
Single Box Weight (kg)	5.495
Single Box Height (mm)	389
Single Box Width (mm)	73
Single Box Depth (mm)	482
Single Box Volume	0.013687354
Outer Box Qty	2
Outer Box Weight (kg)	11.55
Outer Box Height (mm)	407
Outer Box Width (mm)	167
Outer Box Depth (mm)	542
Outer Box Volume	0.036839198
UNSPSC Code	39111704

Additional Information	
Beam Angle	110°
Power Factor	0.9
Windage	0.133m <sup>2</sup>
Bat Safe	Yes - only at 3000K
Flex	1.5m

Beam Angle	110°
Power Factor	0.9
Windage	0.133m <sup>2</sup>
Bat Safe	Yes - only at 3000K
Flex	1.5m