

## skylineomni

### Skyline Omni 100/120/150W Wattage Switchable LED Floodlight with Photocell Switch - Asymmetric - 3CCT

**Part Code: 72050**

The Skyline Omni is a CCT Floodlight with Wattage Switchability in higher wattage models, featuring a compact design, adjustable bracket and tempered glass cover.

- Bat safe at 3000K
- Replaceable Slim Front Frame
- Versatile Angled Adjustable Bracket
- Die-cast Aluminium Housing
- Pre-wired with 1m Lead



**7 Year**  
Guarantee



**50,000**  
Life Hours



**80**  
CRI



**Colour**  
Switchable





**Product Category** Fittings / LED Floodlights

**Application** LED Floodlight

**Product Warranty** 7 Years

**EAN** 5063695005052

**Commodity Code** 9405423990

**Country of Origin** CN

### Technical Specification

|                                |  |
|--------------------------------|--|
| Wattage (W)                    | 100/120/150  |
| Volts (V)                      | 220/240  |
| Colour Temperature (K)         | 3000/4000/5000   |
| Lumen Output (lm)              | 100W = 13841 (3000K) / 15737 (4000K) / 14120 (5000K) - 120W = 16610 (3000K) / 18884 (4000K) / 16944 (5000K) - 150W = 20763 (3000K) / 23605 (4000K) / 21180 (5000K) |
| Lumens per Watt (lm/W)         | 138-157  |
| CRI (ra)                       | 80   |
| Frequency (Hz)                 | 50/60  |
| LED Drive Current              | 740mA at 230V  |
| Energy Consumption (kWh/1000h) | 150  |
| Life Hours                     | 50000  |
| Switching Cycles               | 25000  |
| IK Rating                      | IK08   |
| IP Rating                      | IP65   |
| Operating Temperature          | -40°C - +45°C  |

### Packaging Information

|                                |              |
|--------------------------------|--------------|
| Minimum Order Quantity         | 1            |
| Height (mm)                    | 482          |
| Width (mm)                     | 373          |
| Depth (mm)                     | 69           |
| Individual Product Weight (kg) | 5.225        |
| Single Box Weight (kg)         | 5.495        |
| Single Box Height (mm)         | 389          |
| Single Box Width (mm)          | 73           |
| Single Box Depth (mm)          | 482          |
| Single Box Volume              | 0.013687354  |
| Outer Box Qty                  | 2            |
| Outer Box Weight (kg)          | 11.55        |
| Outer Box Height (mm)          | 407          |
| Outer Box Width (mm)           | 167          |
| Outer Box Depth (mm)           | 542          |
| Outer Box Volume               | 0.0356839198 |
| UNSPSC Code                    | 39111704     |

| Additional Information |                     |
|------------------------|---------------------|
| Power Factor           | 0.9                 |
| Windage                | 0.133m <sup>2</sup> |
| Bat Safe               | Yes - only at 3000K |
| Flex                   | 1.5m                |