

skylineomni

Skyline Omni 200/250/300W Wattage Switchable LED Floodlight with Photocell Switch - Symmetric - Loop In Loop Out - 3CCT

Part Code: 72052

The Skyline Omni is a CCT Floodlight with Wattage Switchability in higher wattage models, featuring a compact design, adjustable bracket and tempered glass cover.

- Bat safe at 3000K
- Precise light distribution - advanced refractive optics with built in reflector
- High durability - 6mm tempered glass and IK08 rating
- Adjustable angled bracket with high strength
- Ease of installation - loop-in loop-out facility



7 Year
Guarantee



50,000
Life Hours



80
CRI



Colour
Switchable





Product Category Fittings / LED Floodlights

Application LED Floodlight

Product Warranty 7 Years

EAN 5063695005557

Commodity Code 9405423990

Country of Origin CN

Technical Specification

Wattage (W)	200/250/300
Volts (V)	220/240
Colour Temperature (K)	3000/4000/5000
Lumen Output (lm)	200W = 27031 (3000K) / 32518 (4000K) / 29476 (5000K) - 250W = 33789 (3000K) / 40648 (4000K) / 36845 (5000K) - 300W = 40547 (3000K) / 48777 (4000K) / 44214 (5000K)
Lumens per Watt (lm/W)	135-163
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	1470mA at 230V
Energy Consumption (kWh/1000h)	300
Life Hours	50000
Switching Cycles	25000
IK Rating	IK08
IP Rating	IP66
Operating Temperature	-40°C - +45°C

Packaging Information

Minimum Order Quantity	1
Height (mm)	515
Width (mm)	440
Depth (mm)	77
Individual Product Weight (kg)	9.6
UNSPSC Code	39111704

Additional Information	
Power Factor	0.9
Windage	0.133m ²
Bat Safe	Yes - only at 3000K
Flex	1.5m