

Cityline Rego

Cityline Rego 30/45/60/75W Street Light - 10m Flex - 3 Pin NEMA - Power-off Disconnecter - CCT

Part Code: 72072

The Cityline Rego brings sleek urban styling together with powerful, efficient LED performance for modern city landscapes.

- Sturdy die-cast aluminium construction & excellent heat dissipation
- Tiltable head to allow for tailored light distribution
- In-built 76mm & 60mm spigot suitable for both pole top & side entry installation
- Embedded breather valve, power off disconnecter, 10KV surge protection to aid safe installation
- 10m pre-wired cable lead



Cityline Rego



Product Category Fittings / LED Street Lights

Application Street Lighting

Product Warranty 8 Years

EAN 5063695041357

Commodity Code 9405423990

Country of Origin CN

Technical Specification

Wattage (W)	30/45/60/75
Volts (V)	220/240
Colour Temperature (K)	3000/4000/5000
Lumen Output (lm)	30W = 5010 (3000K) / 5490 (4000K) / 5340 (5000K) - 45W = 7155 (3000K) / 8055 (4000K) / 7650 (5000K) - 60W = 9000 (3000K) / 10440 (4000K) / 9660 (5000K) - 75W = 10875 (3000K) / 12825 (4000K) / 11550 (5000K)
Lumens per Watt (lm/W)	145-183
CRI (ra)	70
Frequency (Hz)	50/60
LED Drive Current	310-370mA
Energy Consumption (kWh/1000h)	75
Life Hours	100000
Switching Cycles	100000
IK Rating	IK08
IP Rating	IP66

Packaging Information

Minimum Order Quantity	1
Height (mm)	108
Width (mm)	200
Length (mm)	562
Individual Product Weight (kg)	7.4
Single Box Height (mm)	225
Single Box Width (mm)	582
Single Box Depth (mm)	149
Single Box Volume	0.01951155
UNSPSC Code	39111608

Cityline Rego

Construction

Driver Manufacturer	MOSO
Primary Material	Aluminium

Electrical Information

Electric Class	Class I
----------------	---------

Cityline Rego

Additional Information

Power Factor	>0.95
Total Harmonic Distortion	<10%
Standard Deviation Colour Matching	5-step MacAdam ellipse
Flex	10m