

# Cityline Rego

## Cityline Rego 140/160/180/200W Street Light - 10m Flex - 3 Pin NEMA - Power-off Disconnecter - CCT

### Part Code: 72075

The Cityline Rego brings sleek urban styling together with powerful, efficient LED performance for modern city landscapes.

- Sturdy die-cast aluminium construction & excellent heat dissipation
- Tiltable head to allow for tailored light distribution
- In-built 76mm & 60mm spigot suitable for both pole top & side entry installation
- Embedded breather valve, power off disconnecter, 10KV surge protection to aid safe installation
- 10m pre-wired cable lead



# Cityline Rego



**Product Category** Fittings / LED Street Lights

**Application** Street Lighting

**Product Warranty** 8 Years

**EAN** 5063695041388

**Commodity Code** 9405423990

**Country of Origin** CN

## Technical Specification

Wattage (W)	140/160/180/200
Volts (V)	220/240
Colour Temperature (K)	3000/4000/5000
Lumen Output (lm)	140W = 23380 (3000K) / 25620 (4000K) / 24920 (5000K) - 160W = 25440 (3000K) / 28640 (4000K) / 27200 (5000K) - 180W = 27000 (3000K) / 31320 (4000K) / 28980 (5000K) - 200W = 29000 (3000K) / 34200 (4000K) / 30800 (5000K)
Lumens per Watt (lm/W)	145-183
CRI (ra)	70
Frequency (Hz)	50/60
LED Drive Current	770-930mA
Energy Consumption (kWh/1000h)	200
Life Hours	100000
Switching Cycles	100000
IK Rating	IK08
IP Rating	IP66

## Packaging Information

Minimum Order Quantity	1
Height (mm)	108
Width (mm)	300
Length (mm)	766
Individual Product Weight (kg)	10.2
Single Box Height (mm)	340
Single Box Width (mm)	800
Single Box Depth (mm)	160
Single Box Volume	0.04352
UNSPSC Code	39111608

# Cityline Rego

## Construction

Driver Manufacturer	MOSO
Primary Material	Aluminium

## Electrical Information

Electric Class	Class I
----------------	---------

# Cityline Rego

## Additional Information

Power Factor	>0.95
Total Harmonic Distortion	<10%
Standard Deviation Colour Matching	5-step MacAdam ellipse
Flex	10m