



LED CCT Wallpack

Muro 22W LED CCT Wallpack - Emergency - Casambi Dimming Enabled Part Code: 82050

Designed to be used where the aesthetics of the light fitting, along with a tough robust construction, is needed. The fittings are IP65 and IK8 compliant, supplied complete with an opal diffuser for even light distribution.

- Bat safe at 3000K
- Genuine replacement for 70W Metal Halide & Sodium
- High impact polycarbonate construction
- 68% energy saving



3 Year
Guarantee



1 Year
On-Site Warranty



35,000
Life Hours



IP65
Rated



LED CCT Wallpack



Product Category Fittings / LED Wallpacks

Application External Lighting

Product Warranty 3 Years

EAN 5063695000835

Commodity Code 9405423100

Country of Origin CN

Technical Specification

Wattage (W)	22
Volts (V)	220/240
Colour Temperature (K)	3000/4000/6000
Lumen Output (lm)	2329 (3000K) - 2652 (4000K) - 2418 (6000K)
Lumens per Watt (lm/W)	106-121
Emergency Lumen Output (lm)	163
CRI (ra)	80
Frequency (Hz)	50/60
LED Drive Current	510mA
Energy Consumption (kWh/1000h)	22
Life Hours	35000
Switching Cycles	30000
IK Rating	IK08
IP Rating	IP65
Operating Temperature	-30°C - +35°C
Emergency Wattage (W)	2
Lumen Maintenance Ratio	80

Packaging Information

Minimum Order Quantity	1
Height (mm)	305
Width (mm)	255
Depth (mm)	100
Individual Product Weight (kg)	1.1
Single Box Weight (kg)	1.2
Single Box Height (mm)	310
Single Box Width (mm)	260
Single Box Depth (mm)	105
Single Box Volume	0.00846
Outer Box Qty	10
Outer Box Weight (kg)	13.5
Outer Box Height (mm)	650
Outer Box Width (mm)	550
Outer Box Depth (mm)	280
Outer Box Volume	0.1001
UNSPSC Code	39111612



LED CCT Wallpack

Construction	
Primary Material	Polycarbonate

Electrical Information	
Electric Class	Class II

Installation Information	
Driver Integral?	Yes



LED CCT Wallpack

Additional Information

Beam Angle	113°
LED Chip	Samsung
Bat Safe	Yes - only at 3000K