



Mobile Air Conditioning Systems

Our high performance portable air conditioners feature heat pump technology*, enabling units to both heat and cool at the push of a button. Fitted with easy-roll castors they can be conveniently moved from room to room as required. A ducted exhaust hose is included to vent the hot air to the outside of the building. An adjustable window mounting panel is also supplied to attach the exhaust hose for ease of use. Our portable air conditioning units benefit from an automatic in-built water wheel, and can condense the water out with the exhaust air whilst in cool mode, so there is generally no need to empty the water tank (except in extremely humid conditions).



Cat No.	KYR25CO/LUX	KYR35GW/LUX*	KYR45GW/LUX*
Energy Efficiency Rating Cooling	A	A	A
Energy Efficiency Rating Heating	N/A	A	A
Power Rating (Ph/V/Hz)	1/220-240V/50Hz	1/220-240V/50Hz	1/220-240V/50Hz
Capacity BTU/h (cooling)	9000 (2.6kW)	12000 (3.5kW)	14000 (4.1kW)
Capacity BTU/h (heating)	COOL ONLY	12700 (3.7kW)	16000 (4.6kW)
Power Input W (C/H)	1000	1350/1391	1538/1520
Current Input A (C/H)	4.2	5.5/6.0	8.4/8.5
EER (BTU/hr.w)	2.93	2.6	2.3
COP (w/w)	N/A	2.3	3.0
Noise dB(A)	56	65	65
Dehumidification (L/h)	0.9	1.2	1.5
Airflow (m ³ /h)	300	380	380
Net Dimension (mm) W/D/H	440x335x715	440x335x715	470x370x764
Net Weight (kg)	31	32	36
Max Room Size	30m sq	35m sq	10-46m sq
Max Conservatory Size	15m sq	20m sq	23m sq
Exhaust Hose Length	1.5m	1.5m	1.5m
Exhaust Hose Diameter	150mm	150mm	150mm
Window Extraction Kit	Yes	Yes	Yes



Cat No.	KYREXT1.5M	KYR-55EXT1.5M
1.5m Exhaust hose extension		

Cat No.	KYR-WKBAG
 <p>Universal Bag-Type window kit Suitable for all* windows, the kit secures around the edge using a hook and loop design (all included in the kit). It features 1 Zipper with 2 sliders to secure the exhaust hose between. <small>*If you have an abnormal shape or very large window please call to check first.</small></p>	