



LED Dual Shaver Light


Dual Voltage Shaver Light 6W LED 3000K S14 double ended tubular lamp included

DESCRIPTION

Elevate your bathroom with this functional dual-voltage shaver light, ideal for both domestic and commercial bathrooms. A versatile solution that offers efficient lighting as well as a convenient shaving accessory sockets. This clean and modern shaver light offers 400lm of light with a replaceable LED lamp for easy ongoing maintenance.

FEATURES

- Requires 1 x S15 284mm double ended tubular lamp (included). Fitting is rated at 60W max
- Low energy consumption and prolonged lamp life. Instant start, super bright LED's, 3000K warm colour temperature: offering a pleasing light appearance
- High CRI >80: minimises colour distortion of illuminated objects
- Dual voltage shaver socket and safety isolating transformer: for bathroom use
- Mains isolation upon diffuser removal
- NOTE: the shaver socket will only operate when the light is switched on
- NOTE: bathroom shaver lights are not suitable for toothbrush chargers



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.9 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	50 °C	Average Rated Life	15,000 h
Number of switching cycles	12,500	Construction Materials Line 1	Polycarbonate
Dimensions - Height	57 mm	Dimensions - Width	65 mm
Dimensions - Depth	435 mm	IP Rating	IP20

PRODUCT INFORMATION

Wattage Combined	6W	CCT Combined	3000K
Luminaire Lumens Combined	400 lm	lm/W Combined	67 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.9
Lighting Technology used	LED	Non-Directional or Directional	NDLS



Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Displacement Factor	0.5	CCTI/WATTI: Rated Peak Intensity	127 cd



IP20





IP20

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
LEDSHDVO	Standard	6	3000 K	400 lm	67 lm/W

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	1,006 g
Pallet Layer Qty	120
Pallet Layers	4
Pallet Qty	480
MOM / OPQ	1 / 10

