


**SUBTLE LIGHT CORE IP20 3000K STRIP 8MM TAPE 5M REEL 24V 460LM/M 4W/M INTEGRAL**

ILSTWHIA511E



Elevate the ambience of your spaces with the Integral LED Core Subtle Strip, designed to blend performance and style seamlessly. This 5-metre LED strip delivers superior brightness with excellent energy efficiency. Suitable for dry indoor environments, this LED strip is perfectly suited for applications such as under-cabinet lighting in kitchens, highlighting architectural features in living rooms, or adding a soft glow to bedroom headboards. The 3000K colour temperature offers a warm white light that balances cosiness with clarity, creating a comfortable and inviting atmosphere. With its flexibility and high-quality performance, the Integral LED Core Subtle Strip provides a versatile and reliable lighting solution that transforms any interior into a haven of comfort and style.

**Details**

<b>Barcode:</b>	5055788303312
<b>Quick Order Code:</b>	912602
<b>Category:</b>	Strips
<b>Range Name:</b>	Core
<b>Product Type:</b>	White strip
<b>Market Segment:</b>	Commercial indoor, Residential indoor
<b>Features:</b>	Subtle Light
<b>Warranty (Years):</b>	5

**Physical Data**

<b>Construction:</b>	LED surface mounted on to strip
<b>Strip Cut Points (mm):</b>	50
<b>Max Run Length (m):</b>	5
<b>Placement / Application:</b>	Decorative indoor
<b>Strip length (M):</b>	5
<b>Strip Width (mm):</b>	8

**Electrical Data**

<b>Power Consumption per meter (W/m):</b>	4
<b>Voltage (V):</b>	24
<b>Voltage Range (v):</b>	24
<b>Watts per metre:</b>	3.1W - 6w
<b>Driver Included:</b>	No

**Electric Current:** DC  
**EN:** EN-62031  
**LVD Certified:** Yes

## Light Data

**Luminous efficacy (lm/W):** 115  
**Lumens per meter (lm/m):** 460  
**Correlated Colour Temperature (CCT) (K):** 3000  
**Colour Temperature Name:** Warm White  
**Beam Angle:** 120  
**Colour Rendering Index (CRI):** 80  
**Colour Type:** White  
**LED Size (mm):** 2835  
**LED Type:** Surface mounted device (SMD)  
**LEDs per meter:** 120  
**Lifetime (hours):** 36000  
**Reel Length (m):** 5

## Environment

**EN:** EN-62031  
**LVD Certified:** Yes  
**Hg 0% (Mercury Free):** Yes  
**IP Rating (Ingress Protection):** IP20  
**Lowest Operating Temperature (°C):** -20  
**Maximum Operating Temperature (°C):** 45

## Packaging

**Barcode:** 5055788303312  
**Package Weight (g):** 126  
**Package Length (mm):** 205  
**Package Width (mm):** 190  
**Package Depth (mm):** 12  
**Outer Carton Barcode:** 055788305255  
**Qty per Outer Carton:** 100  
**Outer Carton Length (mm):** 550  
**Outer Carton Width (mm):** 450  
**Outer Carton Depth (mm):** 290  
**Qty per euro pallet:** 2400

**Light Source:** Non-replaceable

