

**12W IP44 LED Bathroom Light**

Polished chrome ceiling/wall light 12W 800lm
LED 3100K IP44

DESCRIPTION

The stylish fitting is ideal for installation in a multitude of situations. Ceiling or wall mounted in a domestic or commercial setting and suitable for bathrooms. Long life, energy efficient alternative to traditional fluorescent luminaires

FEATURES

- Multiple low power LED array & optically optimised diffuser - ensures a soft, even lighting effect with no degradation of light output
- Corrosion resistant stainless steel fixing screws
- 3100K warm colour temperature: offering a pleasing light appearance
- Push fit terminals

GENERAL INFORMATION

Light Source	LED	Colour / Finish	Polished chrome effect
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	1.4 kg
Energy Efficiency Class	G		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	I	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Metal
Construction Materials Line 2	Glass	Dimensions - Height	305 mm
Dimensions - Width	305 mm	Dimensions - Depth	80 mm
IP Rating	IP44		

PRODUCT INFORMATION

Wattage Combined	12W	CCT Combined	3100K
Luminaire Lumens Combined	800 lm	lm/W Combined	67 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Lighting Technology used	LED	Non-Directional or Directional	NDLS





Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Chromaticity coordinates x	0.36
Chromaticity coordinates y	0.362	Stroboscopic effect metric (SVM)	0.0
Flicker Metric (pst)	0.0	R9 colour rendering index	13.0
Survival factor @6000hrs	0.9	Claim LED Replace Fluorescent	FALSE
Spectrum report available	Yes	CCTI/WATTI: Rated Peak Intensity	480 cd



PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
PACIFIC12	Standard	12	3100 K	800 lm	67 lm/W

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	1,681 g
Pallet Layer Qty	35
Pallet Layers	4
Pallet Qty	140
MOM / OPQ	1 / 5

